

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of claims:

Claim 1 (currently amended): A printing machine, comprising:

at least two printing unit groups having drives decoupled from one another and assigned, respectively, to one printing unit group, and having printing units with transfer cylinders; and

compensation elements for compensating for speed differences and positional errors between two printing unit groups, said compensation elements being assigned to a printing unit group being an accepting printing unit group, in order to compensate for transfer errors, said compensation elements being capable of ~~changing a position of a sheet on~~ actively moving a sheet with respect to a surface of a cylinder.

Claim 2 (currently amended): A printing machine, comprising:

at least two printing unit groups having drives decoupled from one another and assigned, respectively, to one printing unit group, and having printing units with transfer cylinders; and

compensation elements for compensating for speed differences and positional errors between two printing unit groups, said compensation elements being assigned to a first transfer cylinder of a printing unit group being an accepting printing unit group, in order to compensate for transfer errors, said compensation elements being capable of ~~changing a position of a sheet on~~ actively moving a sheet with respect to a surface of said first transfer cylinder.

Claim 3 (currently amended): A printing machine for printing sheet material, the printing machine comprising:

at least two printing unit groups having drives decoupled from one another and assigned, respectively, to one printing unit group, and having printing units with transfer cylinders;

a dynamic control device for transferring ~~the~~ printed sheets;
and

compensation elements for compensating for speed differences and positional errors between two printing unit groups, the compensation elements being assigned to a first transfer cylinder of a printing unit group being an accepting printing unit group, in order to compensate for transfer errors, said compensation elements being capable of ~~changing a position of~~

~~the sheet on~~ actively moving a sheet with respect to a surface
of said first transfer cylinder.

Claim 4 (currently amended): A printing machine for printing
sheet-type material, the printing machine comprising:

at least two printing unit groups having drives decoupled from
one another and assigned, respectively, to one printing unit
group, and having printing units with transfer cylinders;

a dynamic control device for transferring ~~the~~ printed sheets;
and

compensation elements for compensating for speed differences
and positional errors between two printing unit groups, said
compensation elements being assigned to a printing unit group
being an accepting printing unit group, in order to compensate
for transfer errors, said compensation elements being capable
of ~~changing a position of a sheet on~~ actively moving a sheet
with respect to a surface of a cylinder.

Claim 5 (currently amended): The printing machine according to
claim 4, wherein ~~the~~ said dynamic control device is connected
for communicating with the printing unit groups so as to
record operating parameters, and is connected for

communicating with ~~the~~ said compensation elements so as to control the transfer.

Claim 6 (currently amended): The printing machine according to claim 4, including sensors selected from the group consisting at least of charge-coupled switching elements, photosensors, electronic and electromagnetic sensors, and assigned to the printing unit groups, for recording operating parameters of the printing unit groups, and for passing said parameters on to data processing elements of ~~the~~ said dynamic control device.

Claim 7 (currently amended): The printing machine according to claim 6, wherein ~~the~~ said sensors are selected from the group ~~thereof~~ consisting of charge-coupled switching elements, photosensors, and electronic and electromagnetic sensors.

Claim 8 (currently amended): The printing machine according to claim 4 3, wherein ~~the~~ said compensation elements have a gripper system which, in order to compensate for a speed difference between two printing unit groups and to correct the position of the printed ~~sheet~~ sheets, is arranged parallel to ~~the~~ said ~~cylinder~~ surface of said first transfer cylinder and axially displaceably on ~~the~~ said first transfer cylinder ~~of the accepting printing unit group~~.

Claim 9 (currently amended): The printing machine according to claim 8, wherein said gripper system ~~comprises~~ includes a dynamic actuator and a gripper bar for picking up the printed sheets, the position of said gripper bar being displaced by said actuator at constant radius in a peripheral direction on ~~the~~ said first transfer cylinder in accordance with the speed difference.

Claim 10 (currently amended): The printing machine according to claim 9, wherein said actuator is an element selected from the group ~~thereof~~ consisting of piezoelectric and magnetostrictive elements.

Claim 11 (currently amended): The printing machine according to claim 4 8, wherein ~~the~~ said transfer cylinders of ~~the~~ said printing unit groups have an arrangement by which, after ~~the~~ a printed sheet has been accepted by ~~the~~ said gripper system of ~~the~~ said first transfer cylinder, the printed sheet is fixed only at one location in ~~the~~ said accepting printing unit group.

Claim 12 (currently amended): The printing machine according to claim 4 9, wherein said gripper bar is axially displaceable in the direction of the axis of rotation of ~~the~~ said first

transfer cylinder for correcting the position of the printed ~~sheet~~ sheets.

Claim 13 (original): A method of transferring printed sheets in a printing machine, which comprises determining a difference in speed between two decoupled printing unit groups, and displacing a gripper system parallel to the surface of a cylinder during the sheet transfer so as to compensate thereby for the difference in speed between the printing unit groups on a first transfer cylinder of an accepting printing unit group.

Claim 14 (original): The method according to claim 13, which includes determining a positional error of the printed sheet on the first transfer cylinder of the accepting printing unit group, and correcting the position of the printed sheet parallel to the cylinder surface and axially displaceably on the first transfer cylinder of the accepting printing unit group.

Claim 15 (original): The method according to claim 13, which includes having the dynamic control device register the operating parameters of the printing unit groups before the printed sheet is transferred, determine differences in speed

and control the compensation elements in a compensatory manner during the sheet transfer.

Claim 16 (original): The method according to claim 13, which includes having the dynamic control device register the position of the printed sheet on the first transfer cylinder of the accepting printing unit group after the sheet transfer, and control the compensation elements in a corrective manner after the sheet transfer.

Claim 17 (original): The method according to claim 13, which includes completing the positional correction before the sheet transfer to the second cylinder of the accepting printing unit group.

Claim 18 (original): The method according to claim 13, which includes, in a first step, wherein a difference in speed is compensated for, displacing the actuator parallel to the cylinder surface of the first transfer cylinder of the accepting printing unit group; in a second step, having the gripper system of the first transfer cylinder of the accepting printing unit group accept the printed sheet from the preceding printing unit group; in a third step, registering the position of the printed sheet and, if necessary, determining a positional correction; in a fourth step, having

the actuator make the positional correction on the first transfer cylinder of the accepting printing unit group; in a fifth step, having the actuator moved into a rest position for the printed sheet transfer to the second cylinder of the accepting printing unit group; and in a sixth step, moving the actuator back into the initial position thereof after the printed sheet transfer to the second cylinder of the accepting printing unit group.